

Levelling compounds/
Grout



ASOCRET-HFF

Floor levelling compound for
mechanically exposed areas.

Problems Solved.



Floor levelling compound for mechanically exposed areas

ASOCRET-HFF

Quickly withstands mechanical loading. Ideal for direct use in interior and exterior areas. In the system with seals for easily created and low-maintenance solutions.

Technical data

Compressive strength*	25 N/mm ² after 24 h 52 N/mm ² after 28 days
Flexural strength*	7 N/mm ² after 28 days
Pot life	30-45 minutes
Application	with stirrer, surface rake and spiked roller
Packaging	20 kg container

* The data applies to +23 °C / 50% relative humidity.



Areas of application

- directly usable surfaces indoors, e.g. hobby rooms, workshops, storage rooms and ancillary rooms
- directly usable surfaces outdoors, e.g. garages and loggias
- easy-care substrate in combination with sealing and coating
- easy-care substrate with a concrete look in combination with impregnation
- for layer thicknesses 3–35 mm

Properties

- 1-component
- Shrinkage compensated
- Rapid setting mortar and quickly able to withstand loads
- High wear and abrasion resistance against air, solid rubber and Vulkolan tyres
- Can be ground and polished

Advantages for the user

Creation of demanding wearing surfaces

Long working time

Safety through working in a predetermined product system

Packed waterproof in a foil sack

SCHOMBURG GmbH & Co. KG
Aquafinstraße 2-8
D-32760 Detmold (Germany)
Telephone +49-5231-953-00
Fax +49-5231-953-333
www.schomburg.com



 **SCHOMBURG**