



REINIT-BM

Art.-No. 4 06303

Machine care

REINIT-BM prevents the adhesion of concrete and mortar residues, does not attack metal or lacquer. Reduces rust formation on the treated metal parts. Regular application of REINIT-BM prolongs the service life of machinery and equipment.

Areas of Application:

REINIT-BM is to be applied, generally when adhesion of concrete or mortar should be prevented. It is especially suitable for construction machinery, mixers, automatic stone manufacturing machines, mixer trucks and tools.

Technical Data:

Colour: yellow
Form: liquid, not dilutable
Density: 0.9 g/cm³
Consumption: 100 - 150 g/m²
Storage: cool and dry, 24 month in the original unopened packaging. Use opened packagings promptly.
Packaging: 1000 l IBCs
210 l drums
25 l cans
10 l cans

Product application:

New equipment has to be sprayed with REINIT-BM before use. Used or soiled building equipment should be cleaned with a high pressure hose before first use. Larger concrete and mortar residues must be removed mechanically and be pretreated with ASO-R005 if necessary. As soon as the metal surface is dry and clean, REINIT-BM is to be applied until saturation and undiluted by suitable painting or spraying equipment.

Important Advice:

Our recommendations are only guidelines. Own suitability tests are absolutely necessary to achieve the correct application.

Please observe a current valid EU Safety Data Sheet.