

BLANKOL-0

Art.-No. 4 06101

Solvent free release and impregnating oil

- no build-up, neutral odour, solvent free impregnating and release oil
- minimiert Quellen und Verspröden von Holzschalungen
- protects steel/iron manufacturing plants as well as steel formwork in general from the formation of rust - therefore preventing rust flecks in the concrete
- biodegradable in accordance with test certificate

Areas of application:

BLANKOL-0 is especially for use in pre-cast concrete manufacturing plants and building yards. BLANKOL-0 is suitable for preservation when out of action for a short period, for impregnating base boards whilst also using as a concrete release agent. The areas of application include large formwork sections, timber formwork, moulds/templates and base boards. Steel formwork may be preheated up to +60°C.

Technical Data:

Colour:	yellowish
Consistency:	liquid
Density:	0.89 g/cm ³
Consumption:	Dependent on the absorption of the substrate 15-50 g/m ²
Storage:	cool and dry, 24 month in the original unopened container. Use opened containers promptly.
Packaging:	1000 l IBCs 210 l drums 25 l kegs

Product application:

BLANKOL-0 is to be applied evenly and as thin as possible onto the clean and dry mould. After spraying, drain off with a mineral oil resistant squeegee if necessary.

Important Advice:

- Suitability tests should be carried out prior to usage.
- Avoid puddles!
- Excessive coating can lead to incrustations and build-ups.
- Heated moulds up to maximum + 60 °C!
- BLANKOL-0 cannot be diluted with water.
- Excess material can be removed with a foam rubber squeegee resistant to mineral oils.

Please observe a valid EU safety data sheet!

GISCODE: BTM 10