



Technical Data Sheet

BLANKOL-Super

Chemically/physically active Release Agent

Art.-No. 4 06107

Fields of Application:

BLANKOL-Super has been designed for use with all large-sized moulds, especially with sealed surfaces. Furthermore, BLANKOL-Super is suitable for steel moulds, even when heated up to + 60° C and for plastic coated moulds.

High-quality results are achieved if BLANKOL-Super is used in particular for fair-faced concrete, precast elements and filigree construction parts.

Properties and Benefits:

BLANKOL-Super acts physically/chemically and does not interfere with the concrete. The release agent reduces the application of stains on the concrete surface when properly applied.

The so created film adheres to the mould surface and is rainproof.

Technical Data:

Colour:	yellow
Form:	liquid
Density:	0.85 g/cm ³
Storage:	Temperature-sensitive, do not ship, store and use at temperatures below +8° C
Shelf-life:	12 months in closed original containers
Packaging:	1,000 l IBCs 210 l drums 25 l kegs

Consumption:

Depending on type of mould:
15 – 50 g/m²

Instructions for Use:

BLANKOL-Super is to be sprayed evenly and as thin as possible onto the clean and dry mould.

New, absorbent moulds (wood) have to be treated repeatedly with BLANKOL-Super prior to initial concreting.

Special Advice:

- Suitability tests should be carried out prior to use.
- Avoid puddles!
- Excessive coating can lead to incrustations and build-ups.
- BLANKOL-Super is not water soluble!
- Heated moulds up to max. + 60° C!
- Surplus material can be drained off with a mineral oil resistant foamed rubber wiper.
- Welding, flying sparks, open fire etc. must be absolutely avoided near freshly sprayed moulds.

Safety Regulation:

Please adhere to the European Safety Data Sheet (MSDS)!