



ASOL-SM

Art.-No. 2 03009

Bituminous smoothing compound, fibre-reinforced

- ready to use
- contains solvent
- asbestos free
- watertight and water impermeable
- resistant to UV rays, weathering and naturally occurring aggressive materials in the ground
- extensively flexible once cured
- for exterior use

Areas of application:

ASOL-SM is suitable for smoothing and repair work in roof areas, on to fibre cement, roofing felt, hot-welded bitumen sheets, lead and zinc.

Technical Data:

Basis: bitumen
Solids content: approx. 73 %
Viscosity: 1000 - 1500 dPas at +20 °C
Consumption: approx. 1.3 kg/m² per 1 mm thickness
Application/substrate temperature: +5 °C to +30 °C
Packaging: 5 kg container
Storage: 12 months when stored cool and dry in the original unopened packaging. Use opened packaging promptly.
Cleaning: Clean tools immediately after use with ASO-R001

Substrate preparation:

The substrate must be dry, free from frost, oil and grease, be load bearing as well as free from adhesion inhibiting materials.

Product preparation:

ASOL-SM is supplied ready for use and can be used directly from the packaging. Application is by trowel or steel float. When fully coated, the thickness should not exceed 3 mm (bubble formation is possible in warmer weather and under direct sunlight).

Important advice:

- Protect areas not being treated with ASOL-SM.
- When storing and using, follow safety measures for handling inflammable solvents.
- ASOL-SM is inflammable, therefore keep the container tightly closed.
- Keep away from sources of ignition - do not smoke.

Please observe a valid EU safety data sheet!

GISCODE: BBP20