

REMICRYL-PREMIUM

Art. No. 4 06463

Film forming concrete impregnator with distinct protective properties

REMICRYL-PREMIUM is a solvent-free concrete impregnation agent based on co-polymers. REMICRYL-PREMIUM clearly intensifies the colour of the concrete surface. REMICRYL-PREMIUM delivers a silk-matt finish and gives the concrete surface very good resistance to different contaminants. The resistance of concrete goods to environmental influences and moss, as well as algae growth is significantly improved by treatment with REMICRYL-PREMIUM. The resistance to frost de-icing chemicals is increased – the tendency to efflorescence is reduced. The product is resistant to alkalis and UV.

Areas of application:

REMICRYL-PREMIUM is applied on the dry side. Always dry before packetizing (e.g. with IR-dryers). It can be used to impregnate

- Paving blocks
- Curbstones
- Paving slabs
- Pre-cast concrete components.

Technical Data:

Colour:	White
Consistency:	Liquid
pH value:	8
Density:	1.04 g/cm ³
Storage:	Frost-free, 6 months in original unopened container, use the opened container promptly
Packaging:	1000-kg container

Consumption:

approx. 80-150 g/m² dependent on the substrate

Application:

REMICRYL-PREMIUM is supplied ready to use and must be applied evenly to the surface to be treated with a roller or a roller system, or using a suitable pressure spray system. It is imperative to avoid the formation of puddles during application!

Notes:

- Avoid puddles forming and multiple or excessively thick application.
- Before applying REMICRYL-PREMIUM, the substrate must be free of oil and lubricants and clear of loose components.
- The substrate temperature should be at least +10 °C.
- Apply to a sample area in advance and determine the optimum consumption.

Please observe valid EU safety data sheets!

GISCODE: M-GF01