

# REMICRYL-TOP

Art. No. 4 06458

## Film forming concrete impregnator with good protective properties

REMICRYL-TOP is a solvent-free concrete impregnation agent based on co-polymers. REMICRYL-TOP clearly intensifies the colour of the concrete surface. REMICRYL-TOP is grease-resistant and gives the concrete surface good resistance to different contaminants. The resistance of concrete goods to environmental influences, moss and algae growth is significantly improved by treatment with REMICRYL-TOP. The resistance to frost de-icing chemicals is increased – the tendency to efflorescence is reduced. The product is UV-resistant.

### Areas of application:

REMICRYL-TOP is applied on the dry side. Always dry before packetizing (e.g. with IR-dryers). It can be used to impregnate

- Paving blocks
- Curbstones
- Paving slabs
- Pre-cast concrete components.

### Technical Data:

Colour:	White
Consistency:	Liquid
pH value:	8
Density:	1.03 g/cm <sup>3</sup>
Storage:	Frost-free and dry, 6 months in the original unopened container, promptly use opened container
Packaging:	1,000-kg container 200-kg drum

### Consumption:

approx. 60–150 g/m<sup>2</sup> dependent on the substrate

### Application:

REMICRYL-TOP is supplied ready to use and must be applied evenly to the surface to be treated with a roller or a roller system, or using a suitable pressure spray system. It is imperative to avoid the formation of puddles during application!

### Notes:

- Avoid puddles forming and multiple or excessively thick application.
- Before applying REMICRYL-TOP, the substrate must be free of oil and lubricants and clear of loose components.
- The substrate temperature should be at least +10 °C.
- Apply to a sample area in advance and determine the optimum consumption.

Please observe valid EU safety data sheets!